

INDUSTRIAL  
OTR  
FORKLIFT  
TIRES

---

Maximizer



## DESCRIPTION

- \* For load capacity and inflation pressure figures on different speed rates, please consult the producer company.
- \*\* Load capacity on standard speed and standard load.
  - Our company is entitled to change any information in this catalogue without prior notice.
  - This catalogue overrides any previous catalogues
  - All figures are for reference; our company cannot be deemed responsible for printing errors.
- \*\*\* The visual content of the catalogue is only representative. To find the compatible tire for your car, please refer to the car service or authorized dealer.

# INDUSTRIAL - OTR - FORKLIFT TIRES

## RADIAL IND. TRAC.



Stx ND31  
(R-4)



Stx ND33  
(R-4)



Stx RD22  
(G-2)



Stx RD22  
(L2/E2)



Stx RD31  
(L-3/G-3)

## LOADER RADIAL



Stx TD41  
(L-4)

## EARTHMOVER/LOADER RADIAL



Stx RD31  
(E-3/L-3)



Stx HD41  
(E-4/L-4)

## EXCAVATOR



SM-38 (E-3)

## FORKLIFT



SM-F20  
(PNEUMATIC)



SM-F30  
(PNEUMATIC)



SM-F40  
(PNEUMATIC)



SOLIDMAX N  
(SOLID)

## COMPACTOR



SM-S2 (R-3)

## SKID STEER



SM-ND NHS



SM-135



SM-140 NHS

## INDUSTRIAL TRACTION



TR-45 (F-3)



SM-130 (R-4)



SM-ND (R-4)



SM-125 (R-4)



TR-60 (I-3)



SM-5 (R-1)



SM-PL (L-2)

## GRADER



SG-200  
(G-2)



SG-300  
(G-2)



SM-E3  
(E3)



SM-60  
(E-3)



Stx CD21  
(E-4)

## EARTHMOVER

## CRANE

## LOADER



SM-57  
(L-3)



SM-60  
(L-3)



SM-70  
(L-3)



SM-70  
(L-4)

## PORT APPLICATION

## TERMINAL



C+STACKER  
(IND-4)



C+STACKER  
SMOOTH  
(IND-4S)



Stx TERMINAL







# Stx ND31 (R-4)

Stx ND31 (R-4) tire has strong radial casing and steel belted construction. It is developed for construction equipment to be used in the areas of agriculture and construction. The directional tread pattern provides excellent traction, longevity, resistance to damage and high carrying capacity. Stx ND31 (R-4) is the right response to agro-industrial heavy duty needs. It is suitable for all digging and loading operations on vehicles such as telehandlers, compact loaders and backhoe loaders.



TYRE SIZE	TT/TL	LOAD INDEX	SPEED INDEX
<b>340/80 R18 (12.5/80 R18)</b>	TL	143	A8/B
<b>340/80 R20</b>	TL	138	A8/B
<b>340/80 R20</b>	TL	144	A8/B
<b>440/80 R24</b>	TL	161	A8/B
<b>480/80 R26</b>	TL	167	A8/B
<b>440/80 R28 (16.9 R28)</b>	TL	156	A8/B
<b>400/70 R20</b>	TL	149	A8/B
<b>405/70 R20</b>	TL	149	A8/B
<b>460/70 R24 (17.5L R24)</b>	TL	159	A8/B



# Stx ND33 (R-4)

Stx ND33 (R-4) is developed and designed to offer perfect traction and long life for compact industrial vehicles such as compact loaders, backhoe loaders and telehandlers. Deep and wide lugs are carefully located on the tread to ensure perfect traction on hard or soft terrains. The wide tread profile provides a balanced feel on every condition and increases the tire's service life by avoiding irregular wear. Reinforced sidewalls offer maximum resistance against cuts and puncture while the steel belts under the tread improve the tire's durability and load capacity



TYRE SIZE	TT/TL	LOAD INDEX	SPEED INDEX
460/70 R24 (17.5L R24)	TL	159	A8/B



# Stx RD22 (G-2)

Stx RD22 (G-2) is an all steel radial tire that promises resistance to tears and wears in worksites and on challenging roads. Specially formulated tread compound and all steel carcass structure of Stx RD22 (G-2) offer longevity. The non-directional pattern design delivers outstanding traction and grip in demanding conditions. Stx RD22 (G-2) is designed especially for grader applications.



TYRE SIZE	STAR RATING	TT/TL	LOAD INDEX	SPEED INDEX
<b>14.00 R24</b>	★	TL	153	A8



# Stx RD22 (L-2/E-2)

Stx RD22 (L-2/E-2) is an all steel radial tire that promises resistance to tears and wears in worksites and on challenging roads. Specially formulated tread compound and all steel carcass structure of Stx RD22 (L-2/E-2) offer longevity. The non-directional pattern design delivers outstanding traction and grip in demanding conditions. Stx RD22 (L-2/E-2) is designed especially for grader applications.



TYRE SIZE	STAR RATING	TT/TL	LOAD INDEX	SPEED INDEX
<b>14.00 R24</b>	<b>★★★</b>	TL	188/169	A2/B



# Stx RD31 (L-3/G-3)

Stx RD31 (L-3 / G-3) is an all steel radial OTR tire that offers ultimate resistance to all kind of damage and is designed to be used on loaders and motor graders. Demonstrates efficient self-cleaning feature thanks to its special grooving geometry. Inter-located blocks keep their integrity on all kind of grounds. Specially designed tread compound minimizes cuts and punctures on semi rough ground conditions while simultaneously reducing heat generation to boost service life and improve wear performance.



TYRE SIZE	STAR RATING	TT/TL	LOAD INDEX	SPEED INDEX
<b>17.5 R25</b>	★	TL	176/153	A2/A8



# Stx TD41 (L-4)

It is a high tread depth tire designed for wheel loaders. The tread pattern and carcass structure are especially designed for marble quarries and mine sites. With its specially developed tread mixture and reinforced heel structure, it provides high performance in fields where traction and grip are high.



TYRE SIZE	STAR RATING	TT/TL	LOAD INDEX	SPEED INDEX
26.5 R25	★★	TL	209	A2
29.5 R25	★★	TL	216	A2



# Stx RD31 (E-3/L-3)

Stx RD31 (E-3 / L-3) is an all steel radial OTR tire that offers ultimate resistance to all kind of damage and is designed to be used on loaders and articulated trucks. Demonstrates efficient self-cleaning feature thanks to its special grooving geometry. Inter-located blocks keep their integrity on all kind of grounds. Specially designed tread compound minimizes cuts and punctures on semi rough ground conditions while simultaneously reducing heat generation to boost service life and improve wear performance.



TYRE SIZE	STAR RATING	TT/TL	LOAD INDEX	SPEED INDEX
17.5 R25	★★	TL	182 / 167	A2 / B
20.5 R25	★★	TL	193 / 177	A2 / B
23.5 R25	★★	TL	201 / 185	A2 / B
26.5 R25	★★	TL	209 / 193	A2 / B
29.5 R25	★★	TL	216 / 200	A2 / B



# Stx HD41 (E-4/L-4)

It is especially designed for Articulated Haulers and can also be used in wheel loaders. It is a multi-purpose tire with high tread depth. It provides a long-lasting performance by providing excellent resistance to cuts and heat with its honeycomb-shaped block pattern structure and specially developed tread mixture.



TYRE SIZE	STAR RATING	TT/TL	LOAD INDEX	SPEED INDEX
23.5 R25	★★	TL	201/185	A2/B
26.5 R25	★★	TL	209/193	A2/B
29.5 R25	★★	TL	216/200	A2/B



# SM-38 (E-3)

SM-38 is specially developed for road construction excavators. Its aggressive tread pattern delivers outstanding traction and enables excellent self-cleaning. Promises high resistance to cuts and tears and thus, ensures longevity thanks to its reinforced carcass structure.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>7.50-20</b>	10	TT	123 / 122	B
<b>9.00-20</b>	14	TT	140 / 137	B
<b>10.00-20</b>	16	TT	146 / 143	B



# SM-F20 (PNEUMATIC)

SM-F20 is designed for general purpose tasks. Its strong carcass structure and bead construction provide high performance and durability against impacts.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>4.00-8</b>	8	TT	94	A5
<b>5.00-8</b>	10	TT	111	A5
<b>18x7-8</b>	16	TT	125	A5
<b>6.00-9</b>	12	TT	121	A5
<b>21x8-9</b>	14	TT	131	A5
<b>6.50-10</b>	12	TT	125	A5
<b>23x9-10</b>	20	TT	142	A5
<b>7.00-12</b>	14	TT	134	A5
<b>27x10-12</b>	14	TT	143	A5
<b>23x5-13</b>	10	TT	121	A5
<b>8.15-15</b>	14	TT	146	A5
<b>8.25-15</b>	16	TT	149	A5



# SM-F30 (PNEUMATIC)

SM-F30 delivers high maneuverability thanks to its reinforced tread block pattern. Offers high performance on the field with its strong carcass structure and reinforced bead design. Provides excellent durability feature and resistance against cuts and wears.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>4.00-8</b>	8	TT	94	A5
<b>5.00-8</b>	10	TT	111	A5
<b>16x6-8</b>	16	TT	113	A5
<b>18x7-8</b>	16	TT	125	A5
<b>21x8-9</b>	14	TT	131	A5
<b>6.00-9*</b>	12	TT	121	A5
<b>6.50-10*</b>	12	TT	125	A5
<b>23x9-10</b>	20	TT	142	A5
<b>7.00-12*</b>	14	TT	134	A5
<b>27x10-12</b>	14	TT	143	A5
<b>23x5-(13)</b>	10	TT	121	A5
<b>7.50-15</b>	14	TT	144	A5
<b>8.15-15*</b>	14	TT	146	A5
<b>250-15</b>	20	TT	155	A5
<b>300-15</b>	20	TT	164	A5

\*Extra Durable



# SM-F40 (PNEUMATIC)

SM-F40 offers ultimate durability with its extra tread depth. Center reinforced block structure provides exceptional maneuverability especially while spot turnings. Resistant to cuts and chunking thanks to its strong carcass structure.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>6.00-9*</b>	12	TT	121	A5
<b>6.50-10*</b>	12	TT	125	A5
<b>7.00-12*</b>	14	TT	134	A5
<b>8.15-15*</b>	14	TT	146	A5
<b>8.25-15*</b>	16	TT	152	A5

\*Extra Durable



# SOLIDMAX N (SOLID)

SOLIDMAX N is developed to offer extended service life and minimized maintenance costs for forklifts operating on even surfaces. The premium rubber compound provides excellent wear behavior and extreme resistance to cuts, chips and wear. The cushion layer ensures that toughness does not lead to compromises on operator's comfort and forklift's service life. Steel bead wires embedded in the hard base compound guarantees integrity by preventing the tire from rotating on the rim.



TYRE SIZE	RECOM.	BEAD*	LOAD INDEX	SPEED INDEX
<b>4.00-8</b>	3.00-D	Q/N	97	A5
<b>5.00-8</b>	3.25I-8	Q/N	111	A5
<b>15x4.5-8</b>	3.00D-8	Q/N	100	A5
<b>16x6-8</b>	4.33R-8	Q/N	113	A5
<b>18x7-8</b>	4.33R-8	Q/N	125	A5
<b>6.00-9</b>	4.00E-9	Q/N	121	A5
<b>21x8-9</b>	6.00E-9	Q/N	134	A5
<b>23x9-10</b>	6.50F-10	Q/N	142	A5
<b>140/55-9</b>	4.00-E	Q/N	104	A5
<b>6.50-10</b>	5.00F-10	Q/N	128	A5
<b>23x10-12</b>	8.00G-12	Q/N	145	A5
<b>200/50-10</b>	6.50F-10	Q/N	130	A5
<b>27x10-12</b>	8.00G-12	Q/N	146	A5
<b>7.00-12</b>	5.00S-12	Q/N	136	A5
<b>8.15-15</b>	7.0-15	Q/N	142	A5
<b>8.25-15</b>	6.5-15	Q/N	153	A5
<b>250-15</b>	7.0-15	Q/N	153	A5

Q: Quick  
N: Normal

\*For each tire size of the Solidmax N (Solid) forklift tires, there are two options: Quick Fit and Normal Fit.

# SM-S2 (R-3)

SM-S2 (R-3) is specially designed for compactors applications. Delivers high impact resistance when used in paving applications. Offers outstanding longevity thanks to its strong carcass structure.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>23.1-26</b>	12	TL	162	A8
<b>23.1-26</b>	14	TL	166	A8



# SM-ND NHS

Designed for general purpose use in construction applications. Delivers exceptional traction thanks to its directional pattern design and robust lugs. Strong carcass structure enhances resistance to cuts, tears and wears. Offers outstanding cost efficiency.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>10-16.5 NHS</b>	8	TL	131	A3
<b>12-16.5 NHS</b>	10	TL	142	A3



# SM-135

Skid steer tire solution for harsh, off-road applications. Delivers enhanced durability, traction and side impact resistance for excellent value, performance and low operating costs.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>10-16.5 NHS</b>	12	TL	138	A3
<b>12-16.5 NHS</b>	14	TL	147	A3



# SM-140 NHS

Skid steer tire solution for harsh, off-road applications. Delivers enhanced durability, traction and side impact resistance for excellent value, performance and low operating costs.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>10-16.5 NHS</b>	12	TL	138	A3
<b>12-16.5 NHS</b>	14	TL	147	A3



# TR-45 (F-3)

It is developed for front axles of 2WD industrial tractors and compact earthmovers for the purpose of usage in agricultural areas and worksites. Moreover, it is multi-purpose, low-profile tire that can be used on trailers for on or off road. It provides resistance and longevity against to tears and wears on hard soil, asphalt, and concrete with its specially formulated tread compound and reinforced carcass structure.



TYRE SIZE	TT/TL	LOAD INDEX	SPEED INDEX
<b>11L-16 SL</b>	TL	116	A8



# SM-I30 (R-4)

SM-I30 is an R-4 pattern designed to provide ultimate traction and durability for compact loaders, backhoe loaders and telehandlers. Wide and deep lugs are purposefully located to maximize traction on challenging terrains and ensure maximum durability against cuts and damages. Guarantees consistent performance throughout the tire's long lifespan with wide tread profile that improves the tire's resistance against irregular wear. The number and angles of undertread plies are specifically determined to improve lateral stability.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>16.0/70-20</b>	16	TL	156	A8



# SM-ND (R-4)

Designed for general purpose use in construction applications. Delivers exceptional traction thanks to its directional pattern design and robust lugs. Strong carcass structure enhances resistance to cuts, tears and wears. Offers outstanding cost efficiency.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>10.0/75-15.3</b>	12	TL	126	A8
<b>11.5/80-15.3</b>	12	TL	135	A8
<b>10.5/80-18</b>	12	TL	134	A8
<b>280/80-18</b>	12	TL	134	A8
<b>14.5-20</b>	14	TL	143	D
<b>16.0/70-20</b>	14	TT	154	A8
<b>405/70-20</b>	14	TT	154	A8
<b>16.0/70-24</b>	14	TL	152	B
<b>405/70-24</b>	14	TL	152	B
<b>480/80-26</b>	12	TL	156	A8
<b>23.1-26</b>	14	TL	166	A8



# SM-I25 (R-4)

Specially designed for backhoe and telehandler applications. Offers ultimate resistance to cuts, tears, chips and chunks with its exceptional tread compound and wide lugs. Strong carcass structure ensures longevity.



TYRE SIZE	PR	TT/TL	LOAD INDEX		TYRE SIZE	PR	TT/TL	LOAD INDEX	
			INDEX	SPEED INDEX				INDEX	SPEED INDEX
<b>16.5/85-24</b>	12	TL	149	A8	<b>14.5-20</b>	14	TT	143	D
<b>16.5/85-24</b>	16	TL	156	A8	<b>14.5-20</b>	14	TL	143	D
<b>12.5/80-18</b>	14	TL	146	A8	<b>16.9-24</b>	12	TL	149	A8
<b>340/80-18</b>	12	TL	142	A8	<b>16.9-24</b>	14	TL	152	A8
<b>440/80-24</b>	12	TL	149	A8	<b>19.5L-24</b>	12	TL	151	A8
<b>480/80-26</b>	14	TL	158	A8	<b>18.4-26</b>	12	TL	156	A8
<b>440/80-28</b>	12	TL	152	A8	<b>18.4-26</b>	14	TL	158	A8
<b>16.0/70-20</b>	14	TL	154	A8	<b>18.4-26</b>	16	TL	160	A8
<b>16.0/70-20</b>	16	TL	156	A8	<b>16.9-28</b>	12	TT	152	A8
<b>405/70-20</b>	14	TL	154	A8	<b>16.5/85-28</b>	12	TL	152	A8
<b>405/70-24</b>	14	TL	152	B	<b>16.9-28</b>	14	TL	156	A8
<b>16.0/70-24</b>	14	TL	152	B					



# TR-60 (I-3)

TR-60 (I-3) tire designed for heavy duty tractor applications. Reinforced carcass structure provides exceptional durability and ensures longevity. Features excellent self-cleaning properties and outstanding grip in challenging off the road conditions. The tread pattern provides excellent stability during operations.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>15.5/80-24 RF</b>	12	TL	157 / 145	A8
<b>15.5/80-24 RF</b>	16	TL	163 / 151	A8

RF: REINFORCED



# SM-5 (R-1)

Suitable for small loader, backhoe and telehandler applications. The special tread design offers exceptional traction. Offers outstanding durability thanks to its special compound.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>18.4-26</b>	14	TL	145	A8
<b>16.9-30</b>	14	TL	153	A8



# SM-PL (L-2)

The ideal tire for compact machinery applications. Deep tread depth and directional tread pattern enhance traction in challenging off the road conditions. Offers excellent self-cleaning feature with its special lug design.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>15.5-25</b>	12	TL	149	B



# SG-200 (G-2)

Specially designed for grader and construction machinery applications. Offers excellent durability thanks to its solid tread center structure. Strong nylon carcass structure promises resistance against cuts, chunks and tears. Delivers outstanding traction in challenging conditions with its open shoulders.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>13.00-24</b>	12	TT	143	A8
<b>13.00-24</b>	12	TL	143	A8
<b>13.00-24</b>	16	TL	151	A8
<b>13.00-24</b>	16	TL	151	A8
<b>14.00-24</b>	16	TT	153	A8
<b>14.00-24</b>	16	TL	153	A8



# SG-300 (G-2)

Designed for grader and construction machinery applications. Special tread compound increases service life and improves cut resistance. Delivers enhanced durability, traction and side impact resistance and reduces operating costs. Strengthened bead and body structure makes it suitable for being retreaded.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>16.00-24</b>	16	TL	160	A8



# SM-E3 (E3)

Offers reliable performance in challenging off road conditions. Ensures resistance against chips and chunks thanks to its durable nylon carcass construction. Massive cross lugs and provides excellent traction with wide ground contact.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>14.00-24</b>	16	TT	153	D
<b>14.00-24</b>	20	TL	157	D
<b>14.00-24</b>	24	TT	160	D
<b>14.00-24</b>	28	TT	168	D
<b>14.00-24</b>	28	TL	168	D
<b>14.00-24</b>	32	TT	170	D
<b>14.00-24</b>	32	TL	170	D



# SM-60 (E-3)

Delivers outstanding grip in construction sites thanks to its non-directional tread pattern design. The tread compound improves cut and chip resistance. Offers ultimate durability thanks to solid tread center structure and strong nylon carcass.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>16.00-25</b>	32	TL	177	B
<b>18.00-25</b>	32	TL	183	B
<b>18.00-25</b>	40	TL	187	B
<b>18.00-33</b>	32	TL	188	B
<b>18.00-33</b>	40	TL	214	A5



# Stx CD21 (E-2)

An industrial crane tire developed for mixed service (On/Off Road) usage. Designed to provide comfort on asphalt and superior traction in challenging construction site conditions. Offers outstanding traction and self-cleaning for off-road use, while ensuring a smooth ride on regular roads. It's durable enough for construction sites and delivers excellent traction and braking on any surface, extending its lifespan.



TYRE SIZE	STAR RATING	TT/TL	LOAD INDEX	SPEED INDEX
445/95 R25	★★★	TL	174	F



# SM-57 (L-3)

Offers reliable performance in challenging off road conditions. Its durable nylon carcass construction ensures resistance against chips and chunks. Massive cross lugs and wide ground contact provides excellent traction.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>17.5-25</b>	12	TL	171	A2
<b>17.5-25</b>	16	TT	177	A2
<b>17.5-25</b>	16	TL	177	A2
<b>17.5-25</b>	20	TL	181	A2



# SM-60 (L-3)

Delivers outstanding grip in construction sites thanks to its non-directional tread pattern design. The tread compound ensures excellent cut and chip resistance. Provides outstanding durability thanks to its solid tread center structure and strong nylon carcass.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>17.5-25</b>	16	TL	177	A2
<b>20.5-25</b>	20	TL	186	A2
<b>23.5-25</b>	20	TL	191	A2
<b>23.5-25</b>	24	TL	196	A2
<b>26.5-25 CR</b>	28	TL	203	A2
<b>26.5-25 CR</b>	32	TL	206	A2
<b>29.5-25 CR</b>	28	TL	207	A2
<b>29.5-25 CR</b>	32	TL	210	A2

CR: Cut Resistance

## UNDER DEVELOPMENT

**29.5-25 34PR**



# SM-70 (L-3)

Delivers optimized performance on all terrains. The special compound and aggressive design of the tread pattern enhances handling throughout its exceptionally long life. Provides outstanding resistance to cuts and wears. Specifically designed to offer ultimate performance when excellent traction is needed.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>15.5-25</b>	12	TL	168	A2
<b>17.5-25</b>	16	TL	177	A2
<b>17.5-25</b>	20	TL	181	A2
<b>20.5-25</b>	20	TL	186	A2
<b>23.5-25</b>	20	TL	191	A2
<b>23.5-25</b>	24	TL	196	A2
<b>26.5-25 CR</b>	28	TL	203	A2
<b>26.5-25 CR</b>	32	TL	206	A2
<b>29.5-25 CR</b>	28	TL	207	A2
<b>29.5-25 CR</b>	32	TL	210	A2

CR: Cut Resistance



# SM-70 (L-4)

Delivers outstanding grip in construction sites thanks to its non directional tread pattern design. The tread compound ensures excellent cut and chip resistance. Provides outstanding durability thanks to its solid tread center structure and strong nylon carcass.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>26.5-25 CR</b>	32	TL	206	A2
<b>29.5-25 CR</b>	28	TL	207	A2

CR: Cut Resistance



# C+STACKER (IND-4)

Specially designed for port applications. Deep and non-directional tread design delivers excellent traction and ensures long operating hours. Offers excellent durability features and high resistance against cuts, chunks and wears. Wide centerline enables riding comfort.



IMPROVED



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>18.00-25</b> free axle	40	TL	207	A5
<b>18.00-25</b> drive axle	40	TL	207	A5



# C+STACKER SMOOTH (IND-4S)

Smooth treaded tire for port applications. Optimized tread compound offers outstanding resistance to wear and ensures exceptional longevity. Promises high stability thanks to its smooth tread design. Highly resistant to abrasion.



TYRE SIZE	PR	TT/TL	LOAD INDEX	SPEED INDEX
<b>18.00-25</b> free axle	40	TL	207	A5
<b>18.00-25</b> drive axle	40	TL	207	A5



# Stx TERMINAL

Smooth treaded tire for port applications. Optimized tread compound offers outstanding resistance to wear and ensures exceptional longevity. Promises high stability thanks to its smooth tread design. Highly resistant to abrasion.



TYRE SIZE	TT/TL	LOAD INDEX	SPEED INDEX
<b>310/80 R22.5</b>	TL	175	A8





